

Bass


BN12-300S (4)





12-inch bass speakers deliver an ideal combination of responsiveness androck solid low end. This highly efficient, lightweight neodymium speaker isstrong performer whatever your rhythmic style.

Frequency Response



General Specifications

Nominal diameter	12", 304.8mm
Power rating	300W
Nominal impedance	4
Sensitivity	99dB
Magnet type	Neodymium
Voice coil diameter	2.5", 63.5mm
Coil material	Copper
Cone material	Kevlar loaded paper
Former material	Polyimide
Surround material	Cloth-sealed
Frequency range	50-4000Hz
Xmax	0.098", 2.5mm
Gap depth	0.31", 8mm
Voice coil winding width	0.51", 13mm

Small Signal Parameters

D	0.26m/10.2in
Fs	51.4Hz
Mms	48.31g/1.7oz
Mmd	41.39g/1.46oz
Qms	3.64
Qes	0.395
Qts	0.356
Re	2.72
Vas	80.6lt/2.85cu.ft.
ВІ	10.37Tm
Cms	0.198mm/N
Rms	4.296kg/s
Le (at 1kHz)	0.26mH

Mounting Information

Cut-out diameter	11.1", 283mm
Diameter	12.2", 309mm
Mounting slot dimensions	0.31", 7.9mm Ø
Mounting slot PCD	11.7", 297mm
Number of mounting slots	4
Overall depth	5.2", 132mm
Unit weight	4.4lb, 2.0kg



Celestion, Claydon Business Park, Great Blakenham, Ipswich, IP6 0NL United Kingdom